

- 1 REMOVE AND RETURN TO OWNER.
- 2 LIGHTS ON LOOP CIRCUIT TO BE TEMP. REMOVED PRIOR TO CONSTRUCTION FOR CONT'D. SERVICE. BY OWNER.
- 3 REMOVE CONCRETE WHEEL STOPS AND RETURN TO OWNER.
- 4 TO BE RELOCATED BY OTHERS PRIOR TO DEMOLITION.
- 5 MINIMUM 6" WIDE PROTECTED REESTRIBUTION RIGHT-OF-WAY SHALL BE MAINTAINED IN SCHEDULED DEMOLITION ACCORDINGLY.
- 6 EXISTING TREES PROTECTED AND VALUED FOR MAXIMUM DIVINE CONSERVATION.
- 7 REMOVE SIGNALMANS SIGN SHOWN. FOR MOTOR MAY AT HIS OPTION LEAVE EXISTING CURBS IF PROTECTED, OR REPLACE.
- 8 INITIALLY REMOVE ONLY 4 TO 10 FEET OF SLAB AT WEST SIDE, TO FACILITATE CONSTRUCTION OF NEW SLAB. SLOPELY BEFORE RECONSTRUCTION SLABING SHALL BE DONE.
- 9 REMOVE TOP 4" OF FOOT OF WALL. SAN CUT AT ENDS. REMOVE EARTH FILL PER STRUCK DIMENS.
- 10 REMOVE RETAINING WALL, AND EARTH FILL. CONCRETE, AT NICKER, CUT WALL FLUSH WITH TOP OF ADJACENT SIDEWALK. REMOVE UPPER PART OF ADJACENT SIDEWALK FOOT. BELOW NEW FINISH GRADE.

