



FOUNDATION PLAN BASE BID + ADD ALTERNATE #1
 SCALE: 1/8" = 1'-0" FIN. FLR. ELEV. 99.65 MSL (+0'-0")

DESIGN LOADS

LIVE LOAD	AS INDICATED BY FLOOR
DEAD LOAD	AS INDICATED BY FLOOR
WIND	UBC ZONE 2
STEEL YIELD STRESS	58 KSI
CONCRETE	9 25 DAYS

Note 1: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.
 Note 2: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.
 Note 3: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.
 Note 4: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.

Note 5: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.
 Note 6: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.
 Note 7: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.
 Note 8: All concrete shall be placed in 4" lifts. Reinforcement shall be placed in 4" lifts.

